

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



(11) Publication number: **0 521 717 A3**

(12)

EUROPEAN PATENT APPLICATION

(21) Application number: **92306105.5**

(51) Int. Cl.⁵: **E05B 3/00, E05B 13/10**

(22) Date of filing: **01.07.92**

(30) Priority: **01.07.91 GB 9114193**

(43) Date of publication of application:
07.01.93 Bulletin 93/01

(84) Designated Contracting States:
AT BE CH DE DK ES FR GB GR IT LI LU MC NL PT SE

(88) Date of deferred publication of search report:
03.03.93 Bulletin 93/09

(71) Applicant: **CEGO Limited**
Western Road
Silver End Essex, CM8 3QB (GB)

(72) Inventor: **Hutton, Melvin John**
9 Makemores, Rayne
Braintree, Essex CM7 8TJ (GB)

(74) Representative: **Goodanew, Martin Eric et al**
MATHISEN, MACARA & CO. The Coach House
6-8 Swakeleys Road
Ickenham Uxbridge UB10 8BZ (GB)

(54) **Locking handle.**

(57) A locking handle assembly for a door or window comprises a fixing plate (1), a handle (9) which is pivotally mounted on the fixing plate (1) for movement between open and closed positions, and a catch which automatically engages when the handle (9) is moved into the closed position to prevent subsequent movement of the handle (9) to an open position until the catch is released. The catch comprises a spring loaded plunger (7) which is housed in the fixing plate (1) and is arranged to project from the plate (1) into a recess (18) in the handle (9) to prevent turning of the handle (9) when it is in the closed position, and the handle (9) carries a spring loaded push button (19) which can be depressed to push the plunger (7) out of the recess (18) to allow turning of the handle (9) from the closed position, a portion of the handle (9) engaging the plunger (7) to hold it depressed within the fixing plate (1) in all positions of the handle (9) other than the closed position whether or not the push button (19) is depressed.




Fig.2.

EP 0 521 717 A3




Fig.4.



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number

EP 92 30 6105

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. CL.5)
A	EP-A-0 241 245 (REGENT LOCK) * the whole document *	1-3	E05B3/00 E05B13/10
A	EP-A-0 410 886 (RONIS) * the whole document *	1-4	
			TECHNICAL FIELDS SEARCHED (Int. CL.5)
			E05B
The present search report has been drawn up for all claims			
Place of search BERLIN		Date of completion of the search 07 DECEMBER 1992	Examiner KRABEL A.
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 (12.82) (P0001)